

sales@awaretech.com

# STAT FAX<sup>®</sup> 2200

Programmable Open System

ELISA Microplate - Digital Dry Bath



## Stat Fax<sup>®</sup> 2200 Digital Dry Bath

### Features

- Holds two 96-well microplates.
- Digitally controlled 8-speed mixer with orbital mixing from 575 to 1500 rpm.
- Temperature adjustable from ambient to 40°C with resolution of 0.1°C
- Digital timer controls mixing or can be operated independently, solely as a timer.
- Compact and easy to operate
- Outer tinted cover provides further insulation and protection from light.

### Options & Accessories

Available with either 120V AC or 230V AC adapter.  
37°C temperature calibration plate.

 **AWARENESS<sup>®</sup>**  
TECHNOLOGY, INC.

[www.awaretech.com](http://www.awaretech.com)

# STAT FAX<sup>®</sup> 2200

## ELISA Microplate - Digital Dry Bath

<b>Temperature range</b>	Ambient to 40° C
<b>Resolution</b>	0.1° C
<b>Uniformity with cover</b>	Better than +/- .4° C
<b>Mechanism</b>	Enclosed, warm aluminum bed with air circulation
<b>MIXER</b>	
<b>Speeds</b>	8 gradual steps from 575 to 1500 RPM,
<b>Options</b>	Continuous or pulse
<b>Mechanism</b>	Rotating counter weight
<b>Timer</b>	Set time, view time remaining, audible signal (stop mixing but maintains temperature control after time out)
<b>Modes</b>	
<b>Resolution</b>	1 second
<b>Range</b>	1 second to 99 minutes, 59 seconds
<b>Electronic</b>	
<b>Display</b>	Four 7 segment red LEDs.
<b>Keyboard</b>	16-key, domed membrane switch, enunciating
<b>Power requirements</b>	12 V AC, 2 amps. Adapters available for 120 V or 230 V power with US or Euro plugs
<b>Certifications</b>	NRTL Listed, CE Mark
<b>Vessel</b>	Holds 2 standard microwell plates or strip trays
<b>Dimensions and weight</b>	Approx. 11" x 12.5" x 5.75", 7.2 lbs Approx. 43 cm x 37 cm x 18 cm, 3.3 kg



**Awareness Technology, Inc. USA & International**  
tel: +1 772 283 6540 fax: +1 772 283 8020

**Awareness Technology, Inc. Europe**  
tel: +43 (0) 2236 892465 fax: +43 (0) 2236 892464

**Awareness Technology, Inc. Asia & Africa**  
tel: +971 (06) 557 80 58 fax: +971 (06) 557 80 59

ISO 13485:2016

